English Language Translation of the International Application as Filed Page. 15 of 18

International Application No.: PCT/CN2005/000520 Attorney's Docket Number: WHKY-00101-NUS

## **CLAIMS**

1. A pigment having a color-shifting effect comprising a base material which is alternatively coated with metal oxides of different refractive indexes, and an outer protection layer, wherein said base material is natural mica whose surface is coated with three-layered metal oxides; the first layer is a metal oxide having a high refractive index so as to smooth the step-like mica surface; the second layer is the metal oxide having low refractive index; and the third layer is a metal oxide having a high refractive index.

- 2. The pigment according to claim 1, wherein the thickness of the second metal oxide layer having low refractive index is more than the optical thickness of the 2<sup>nd</sup>-order interference color.
- 3. The pigment according to claims 1 or 2, wherein the thickness of the first metal oxide layer having a high refractive index is the optical thickness of silver-white to golden-yellow interference color.
- 4. The pigment according to claims 1 or 2, wherein the thickness of the second metal oxide layer having a low refractive index is the optical thickness of from the 2<sup>nd</sup>-order green to the 4<sup>th</sup>-order interference color.
- 5. The pigment according to claim 1, wherein the second metal oxide having a low refractive index is SiO<sub>2</sub>.
- 6. The pigment according to claims 1 or 2, wherein the metal oxides having a high

English Language Translation of the International Application as Filed

International Application No.: PCT/CN2005/000520 Attorney's Docket Number: WHKY-00101-NUS

Page. 16 of 18

refractive index are TiO<sub>2</sub>, SnO<sub>2</sub>, Fe<sub>2</sub>O<sub>3</sub>, Fe<sub>3</sub>O<sub>4</sub>, CoO, Co<sub>2</sub>O<sub>3</sub>, ZrO<sub>2</sub>, or Cr<sub>2</sub>O<sub>3</sub> or their mixture or compounds.

- 7. The pigment according to any of claims 1-6, wherein the synthesis of the pigment comprises: putting wet grinded mica powders with specific standards into deionized water and stirring it into a suspension solution; heating it to 60-90°C; then adjusting the pH value to 2-9 with diluted aqueous hydrochloric acid or sodium hydroxide solution; adding a pre-measured amount of dissolvable inorganic salt solution having a high refractive index; keeping its pH value constant by adding hydrochloric acid or sodium hydroxide solution, depositing hydrate metal oxide having high refractive index and the desired thickness on the surface of mica; stirring it for 30 minutes at constant temperature for ageing; adjusting its pH value to 6-4 with sodium hydroxide solution; adding a pre-measured amount of a dissolvable inorganic salt solution having a low refractive index; keeping its pH value constant by adding a hydrochloric acid solution to make the metal oxide having a low refractive index deposit to a desired thickness, stirring it for 30 minutes at constant temperature for ageing; adjusting its pH value to 2-9 with diluted aqueous hydrochloric acid or a sodium hydroxide solution; adding a pre-measured amount of inorganic salt solution having a high refractive index, keeping its pH value by adding a hydrochloric acid or sodium hydroxide solution to obtain the desired tones and zones of color changes; stir it for 30 minutes in constant temperature for ageing; and flitter, cleanse, dry, calcine, sift out and dry.
- 8. The pigment according to claim 7, wherein the dissolvable inorganic solution having a high refractive index is a chlorine-based compound, e.g., TiCl<sub>4</sub>, TiOCl<sub>2</sub>, SnCl<sub>4</sub>,

SnCl<sub>2</sub>, FeCl<sub>3</sub>, FeCl<sub>2</sub>, CoCl<sub>2</sub>, ZrOCl<sub>2</sub> or CrCl<sub>3</sub>.

- 9. The pigment according to claim 7, wherein the dissolvable inorganic metal salt solution having a low refractive index is a hydrate glass compound.
- 10. The pigment according to claim 7-9, wherein an organic or an inorganic ferrous pigment or an outer protection layer can be added.